## **Declaration of Performance**

No. 1102, 1121

Unique identification code of the product type Lithurin Protec

2 Intended use/es EN 1504-2:

Protection against Ingress – impregnation (1.2)

Physical resistance/Surface Improvement - impregnation

CE

3 **AB Lindec** Manufacturer

Address: Box 5, 421 21 Västra Frölunda, Sweden

Telephone: +46 31-29 88 10 Telefax: +46 31-29 88 76 E-mail: info@lindec.se

Authorised representative Not relevant

5 System/s of AVCP EN 1504-2:

System 4 (for uses with low performance requirements in

buildings and civil engineering works)

System 4 for fire behaviour (for uses subject to reaction to

fire regulations)

Harmonised standard EN 1504-2:2004 (ZA.1b, ZA.1c)

Notified body Not relevant for system 4

6b **European Assessment Document** Not relevant **European Technical Assessment** Not relevant

Declared performance/s

Essential characteristics	Performance	Harmonised technical specification
Abrasion resistance	NPD	EN 1504-2:2004
Capillary absorption and permeability to water	> 0,1 kg/m <sup>2</sup> x h <sup>0.5</sup>	EN 1504-2:2004
Impact Resistance	≥ 4 Nm, klass 1	EN 1504-2:2004
Adhesion strength by pull off test	NPD	EN 1504-2:2004
Slip Resistance	MIMIMYVELELE	EN 1504-2:2004
(Dry test)	103, Class II	
(Wet test)	74, Class I & III	
Reaction to fire		EN 1504-2:2004
Depth of penetration	Class I (< 10 mm)	EN 1504-2:2004

NPD = No performance determined

8 Appropriate Technical Documentation and/or

Specific Technical Documentation Not applicable

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above

Gothenburg, 19.06.2019

Signed on behalf of the manufacturer by:

Mikael Voeler **Managing Director**